

## HERMETIC LED FIXTURE ARKOS 3 120CM 70W 4000K 11250LM IP66 MILKY PC DIFFUSER



CODE: C17-HLC3-120A-70B-840B-1B  
EAN: 5900280974228

| Mechanical data           |                                                     |
|---------------------------|-----------------------------------------------------|
| Material                  | Obudowa: PC, klosz: PC                              |
| Color                     | RAL7035                                             |
| Electrical data           |                                                     |
| Nominal voltage           | Un: 230V~50Hz                                       |
| Power consumption         | 70W                                                 |
| Light data                |                                                     |
| Beam angle                | 120°                                                |
| Color rendering index     | CRI>80                                              |
| Color temperature         | 4000K                                               |
| Luminous flux             | 11250lm                                             |
| Installation Data         |                                                     |
| Height                    | 88mm                                                |
| Length                    | 1185mm                                              |
| Width                     | 85mm                                                |
| Certificates and markings |                                                     |
| Energy class              | C                                                   |
| EPREL                     | 1471479                                             |
| Protection class          | Class I                                             |
| Protection degree         | IK08                                                |
| PZH                       | TAK                                                 |
| Warranty                  | 5 years                                             |
| Degree of protection      | IP66                                                |
| Other                     |                                                     |
| Durability                | L70B50: 141000h                                     |
| Installation              | Natynkowy/zwieszany, rozstaw uchwytów: 622 do 788mm |
| Operating temperature     | -20°C /+40°C                                        |
| Power factor              | DF>0,95                                             |

Product type

Źródło światła

Brand

Luxmena