


FUSE HOLDER SERIES

FHD Series Fuse Holder



FHD Series

Fuse Holder and Links



Standard	IEC/EN 60947-3	
Description	Fuse switch disconnecter with LED indicator	
Number of Poles	1P	3P
Fuse size	10x38, 14x51, 22x58	10x38, 14x51, 22x58
Rated operational current Ie (A)	32, 63, 125	32, 63, 125
Rated operational voltage Ue	AC 250V, AC 690V	AC 500V, AC 690V
Rated insulation voltage (V)	AC 500	
Rated impulse withstand voltage (kV)	4	
Conditional short-circuit current (kA)	20	
Utilization category with fuse	g G	
Protection degree	IP20	
Mounting method	DIN rail installation	
Declaration		



FHD-1P-AC250-032



FHD-3P-AC500-032

FHD Series		Fuse Holder and Links				
	Indeks	EAN	Fuse Link	Max link current	Packing unit (holder)	Packing unit (link)
 <p>FHD-1P</p>	FHD-1P-AC250-032	5902138407483	FD-10X38-XXX	32A	12	120
	FHD-1P-AC690-063	5902138407506	FD-14X51-XXX	63A	12	200
	FHD-1P-AC690-125	5902138407520	FD-22X58-XXX	125A	12	200
 <p>FHD-3P</p>	FHD-3P-AC500-032	5902138407490	FD-10X38-XXX	32A	4	120
	FHD-3P-AC690-063	5902138407513	FD-14X51-XXX	63A	4	200
	FHD-3P-AC690-125	5902138407537	FD-22X58-XXX	125A	4	200