

OPRAWA HIGHBAY LED



HIGHBAY LED
HIGHBAY LICHT LED

HBP3 PARIT 3

MATERIAL ► stop aluminium, PC
MATERIAL ► aluminum alloy, PC
MATERIAL ► aluminiumlegierung, PC



do 160lm/W




DALI




Instrukcja MS / RF
MS / RF manual

	a	b
HBP3-100A: Ø235	Ø235	110
HBP3-100D: Ø270	Ø270	115
HBP3-150: Ø270	Ø270	115
HBP3-200: Ø305	Ø305	115
HBP3-240: Ø340	Ø340	124



Opcjonalne uchwyty do montażu ściennego
Optional brackets for wall montage
C85-UM-HB-M10



wymienne soczewki 120° / 90°



radiator odprowadzający ciepło



uchwyt M10 do montażu wiszanego



grawerowana tabliczka znamionowa



zewnętrzny zasilacz



certyfikat PZH

BEMKO	EAN	opakowanie	barwa światła [K]	P _{ON} moc [W]	strumień świetlny (wydajność)	strumień z LED
kod	EAN					
C85-HBP3-100D-090BL	5900280968029	1	4 000	100	16 000lm (160lm/W)	19 100lm
C85-HBP3-150D-090BL	5900280968036	1	4 000	150	24 000lm (160lm/W)	28 600lm
C85-HBP3-200D-090BL	5900280968043	1	4 000	200	32 000lm (160lm/W)	38 100lm
C85-HBP3-240D-090BL	5900280968050	1	4 000	240	38 400lm (155lm/W)	45 700lm
C85-HBP3-100A-120BL	5900280963505	1	4 000	100	16 000lm (160lm/W)	19 100lm
C85-HBP3-150A-120BL	5900280963512	1	4 000	150	24 000lm (160lm/W)	28 600lm
C85-HBP3-200A-120BL	5900280963529	1	4 000	200	32 000lm (160lm/W)	38 100lm
C85-HBP3-240A-120BL	5900280963536	1	4 000	240	38 400lm (155lm/W)	45 700lm
C85-MS-HBP3	5900280975690	1				
C85-RF-HBP3	5900280975706	1				

MIKROFALOWY CZUJNIK RUCHU I ZMIERZCHU DO OPRAW HBP3-xxxx
PILOT RF DO OPRAW HBP3-xxxxA Z MIKROFALOWYM CZUJNIKIEM RUCHU

Gwarancja w zależności od warunków pracy | max. 12h/dobę - 5 lat gwarancji, 24h/dobę - 3 lata gwarancji

www.bemko.eu