

LFC CAMPUS

LED FLOODLIGHT
LED LICHTFLUTER

MATERIAL ► stop aluminium, szkło hartowane
MATERIAL ► aluminum alloy, tempered glass
MATERIAL ► aluminiumlegierung, gehärtetes glas

- 230V
50Hz
- DF
≥0.9
- 3000K
4000K
- CRI
≥70
- 90°
- IK08
- 50000h
- +40°C
-40°C
- IP66



LFC-100DG




LFC-060DG



LFC-030DG

NOWOŚĆ



	a [mm]	b [mm]	c [mm]
LFC-030DG :	270	230	50
LFC-060DG :	320	224	50
LFC-100DG :	421	291	62
LFC-150DG :	421	291	62
LFC-200DG :	520	342	65
LFC-250DG :	520	342	65



diody LED PHILIPS
z wymiennymi
soczewkami



wysoka efektywność
odprowadzania ciepła



niezawodny zasilacz
INVETRONICS



opcjonalne kąty świecenia:
30x30°, 60x60°,
155x75°, 155x95°

Zastosowanie:

- obiekty sportowe, typu orlik
- hale sportowe
- obiekty logistyczne
- otwarte tereny przemysłowe



kod

C66-LFC-030DG-4K-9090
C66-LFC-060DG-3K-9090
C66-LFC-060DG-4K-9090
C66-LFC-100DG-3K-9090
C66-LFC-100DG-4K-9090
C66-LFC-150DG-3K-9090
C66-LFC-150DG-4K-9090
C66-LFC-200DG-3K-9090
C66-LFC-250DG-3K-9090
C66-LFC-250DG-4K-9090



EAN

5900280959287
5900280966902
5900280959294
5900280966919
5900280959300
5900280966926
5900280959317
5900280975812
5900280966933
5900280959324



opakowanie

1/10
1/6
1/6
1/4
1/4
1/4
1/4
1/2
1/2
1/2



barwa światła [K]

4000K
3000K
4000K
3000K
4000K
3000K
4000K
3000K
3000K
4000K



moc [W]

30
60
60
100
100
150
150
200
250
250



strumień
światlny [lm]

3600
8400
8400
15 000
15 000
22 500
22 500
30 000
37 500
37 500