

230/400V
50/60Hz

1P

DIN35


U_{imp}
4kV

I_{cn}
10000A

U_i
400V

IP20

+30°C
-5°C



terminal capacity:
max. 25 mm²



possibility
of sealing



capability to connect
using comb busbars



descriptive box

Schelinger

code

- A02-G9-1P-B02
- A02-G9-1P-B04
- A02-G9-1P-B06
- A02-G9-1P-B10
- A02-G9-1P-B13
- A02-G9-1P-B16
- A02-G9-1P-B20
- A02-G9-1P-B25
- A02-G9-1P-B32
- A02-G9-1P-B40
- A02-G9-1P-B50
- A02-G9-1P-B63
- A02-G9-1P-C02
- A02-G9-1P-C04
- A02-G9-1P-C06
- A02-G9-1P-C10
- A02-G9-1P-C13
- A02-G9-1P-C16
- A02-G9-1P-C20
- A02-G9-1P-C25
- A02-G9-1P-C32
- A02-G9-1P-C40
- A02-G9-1P-C50
- A02-G9-1P-C63



EAN

- 5900280999450
- 5900280999467
- 5900280980205
- 5900280980212
- 5902138401191
- 5900280980229
- 5900280980236
- 5900280980243
- 5900280980250
- 5900280980267
- 5900280980274
- 5900280980281
- 5900280999474
- 5900280999481
- 5900280980311
- 5900280980328
- 5902138401207
- 5900280980335
- 5900280980342
- 5900280980359
- 5900280980366
- 5900280980373
- 5900280980380
- 5900280980397



package

- 1/12/120
- 1/12/120
- 1/12/120
- 1/12/120
- 1/12/120
- 1/12/120
- 1/12/120
- 1/12/120
- 1/12/120
- 1/12/120
- 1/12/120
- 1/12/120
- 1/12/120
- 1/12/120
- 1/12/120
- 1/12/120
- 1/12/120
- 1/12/120
- 1/12/120
- 1/12/120
- 1/12/120
- 1/12/120
- 1/12/120



characteristics

- B
- B
- B
- B
- B
- B
- B
- B
- B
- B
- B
- B
- C
- C
- C
- C
- C
- C
- C
- C
- C
- C
- C

I_n

rated
current [A]

- 2
- 4
- 6
- 10
- 13
- 16
- 20
- 25
- 32
- 40
- 50
- 63
- 2
- 4
- 6
- 10
- 13
- 16
- 20
- 25
- 32
- 40
- 50
- 63