




Characteristics:

A



AC

galvanised steel  
terminals

TEST control button

possibility to connect  
with comb  
busbarsterminal capacity  
25 mm<sup>2</sup>

Schelinger



EAN



package



type

characteristics  
work $I_n$ rated current  
[A] $I_{\Delta n}$ differential current  
[mA]

code	EAN	package	type	characteristics work	rated current [A]	differential current [mA]
A08-GVL-A-B16	5900280973290	1/6/60	A	B	16	30
A08-GVL-A-B25	5900280973306	1/6/60	A	B	25	30
A08-GVL-A-C16	5900280973313	1/6/60	A	C	16	30
A08-GVL-A-C25	5900280973320	1/6/60	A	C	25	30
A08-GVL-AC-B10	5900280983435	1/6/60	AC	B	10	30
A08-GVL-AC-B16	5900280983442	1/6/60	AC	B	16	30
A08-GVL-AC-B20	5900280995223	1/6/60	AC	B	20	30
A08-GVL-AC-B25	5900280983459	1/6/60	AC	B	25	30
A08-GVL-AC-C16	5900280983466	1/6/60	AC	C	16	30
A08-GVL-AC-C20	5900280995230	1/6/60	AC	C	20	30
A08-GVL-AC-C25	5900280983473	1/6/60	AC	C	25	30
A08-GVL-AC-C32	5900280983480	1/6/60	AC	C	32	30